

## CEPRO PVC WELDING CURTAIN

### Description

All Cepro welding curtains comply with EN ISO 25980, the European standard. Cepro welding curtains also have a standard width of 140 cm, are provided with a 5 cm seam all around, 7 suspension eyelets at one 140 cm side and snap-fasteners on both height sides. Thickness 0,40 mm. All standard welding curtains are supplied incl. 7 steel suspension rings.

### Application

Welding curtains are designed for use in workplaces where bystanders must be protected against the hazardous radiation emitted during welding work. They provide protection against dangerous Blue Light and Ultra Violet (UV) rays. In case of prolonged exposure these rays can cause actinic conjunctivitis and even cataracts.

The curtains also protect the welder against the reflection of the welding light. Cepro produces welding curtains in four colours, all complying with the European standard EN ISO 25980.

Cepro products offer protection. They prevent actinic conjunctivitis, cataract, burnt skin, create a safe environment for bystanders and considerably reduce medical costs.

### Conditions for use

Cepro welding curtains are self-extinguishing and therefore withstand welding sparks. They are, however, not suitable as a welding blanket and do not withstand open fire and intense heat. Welding curtains offer visual protection against dangerous radiation but are not suitable for supervising welding works or as a substitute for

### Characteristics

Cepro welding curtains are made of PVC.

### Dimensions

The following standard dimensions are available:

160 x 140 cm 240 x 140 cm  
 180 x 140 cm 260 x 140 cm  
 200 x 140 cm 280 x 140 cm  
 220 x 140 cm 300 x 140 cm

160 x 220 cm 180 x 120 cm  
 180 x 220 cm 180 x 180 cm  
 180 x 240 cm

Made to size curtains are available on request.

