

CEPRO PVC WELDING STRIPS

Description

All Cepro welding strips comply with **EN ISO 25980**, the European standard. Cepro welding strips also have a standard width 300 mm. A full roll has a length of 50 running meter. Available in a thickness of 2 and 3 mm. Cepro welding strips can be cut and punched to the desired length.

Application

We recommend using welding strips for large or frequent mechanical loads. Welding strips are designed for use in workplaces where bystanders must be protected against the hazardous radiation emitted during welding work. They provide protection against dangerous Blue Light and Ultra Violet (UV) rays. In case of prolonged exposure these rays can cause actinic conjunctivitis and even cataracts.

Welding strips also protect the welder against the reflection of the welding light. Cepro produces welding strips in four colours, all complying with the European standard EN ISO 25980.

Cepro products offer protection. They prevent actinic conjunctivitis, cataract, burnt skin, create a safe environment for bystanders and considerably reduce medical costs.

Conditions for use

Cepro welding strips are self-extinguishing and therefore withstand welding sparks. They are, however, not suitable as a welding blanket and do not withstand open fire and intense heat. Welding strips offer visual protection against dangerous radiation but are not suitable for supervising welding works or as a substitute for welding

Characteristics

Cepro welding strips are made of PVC.

Dimensions

The following standard dimensions are available:

300 x 2 mm

300 x 3 mm

Cepro welding strips can be cut to the desired length with the standard Cepro hole pattern.

On special request we can also deliver other widths and thicknesses.

