

LETO WELDING BLANKET

Description

For the Leto heat resistant fabric high quality silica fibres are used, which are environmentally non-hazardous. Leto is treated with a mineral based finish to improve its abrasive resistance and the resistance to fraying. Leto is free of asbestos!

Application

The maximum application temperature is 1000 °C, shortly up to 1300°C.

Conditions for use

- CEPRO recommends the use of multiple layers for maximum protection.
- Always use welding blankets at an angle of at least 15 degrees.
- The temperatures shown are only an indication. The suitability of the selected product should always be tested beforehand.
- Regularly check welding blankets for tears and or other damage. Replace damaged blankets where necessary.
- Welding blankets can be used for many purposes and therefore, no guarantee can be given on their use. The end user is responsible for determining whether the welding blanket is suitable for use in a specific situation and whether it offers sufficient protection during the work to be performed.
- CEPRO welding blankets are sewn on the cut edges with best quality Kevlar thread.

Characteristics

Leto is recommended for horizontal use, for example as a welding and grinding curtain in situations in which very high temperatures are reached. Leto silicate-fabrics have excellent characteristics in relation to handling and resistance to high temperature loads. Therefore this fabric is suitable for use as welding blanket even under extreme conditions.

Available dimensions

Leto welding blanket, 90 x 100 cm	56.51.91
Leto welding blanket, 90 x 200 cm	56.51.92
Leto welding blanket, 180 x 200 cm	56.51.95
Leto welding blanket, 180 x 300 cm	56.51.96
Leto welding blanket, 270 x 300 cm	56.51.97
Part of a roll, width 90 cm	56.51.09.0900
Part of a roll, width 90 cm	56.51.09.0900
Full roll 50 m ¹ , width 90 cm	56.51.09.0950
Made to size welding blanket	56.51.90



Version 001 - Check our website for the latest version.

CEPRO_PFS_Welding blankets_Basic_Leto_1EN_rev