

PALLAS WELDING BLANKET

Description

Pallas product is a fiberglass fabric with an inorganic coating on both sides in order to increase the antislip properties and the heat resistance.

Application

The maximum application temperature is 700 °C, shortly up to 750°C.

Conditions for use

- CEPRO recommends the use of multiple layers for maximum protection.
- Always use welding blankets at an angle of at least 15 degrees.
- The temperatures shown are only an indication. The suitability of the selected product should always be tested beforehand.
- Regularly check welding blankets for tears and or other damage. Replace damaged blankets where necessary.
- Welding blankets can be used for many purposes and therefore, no guarantee can be given on their use. The end user is responsible for determining whether the welding blanket is suitable for use in a specific situation and whether it offers sufficient protection during the work to be performed.
- CEPRO welding blankets are sewn on the cut edges with best quality Kevlar thread.

Characteristics

Pallas is perfect for use as a allround welding blanket. Pallas is ideal to be used cut from the roll, as the cutting edges do not unravel. Pallas is free of asbestos.

Available dimensions

Pallas welding blanket, 100 x 100 cm	56.50.41
Pallas welding blanket, 200 x 100 cm	56.50.42
Pallas welding blanket, 200 x 200 cm	56.50.45
Pallas welding blanket, 200 x 300 cm	56.50.46
Pallas welding blanket, 300 x 300 cm	56.50.47
Pallas welding blanket, 400 x 300 cm	56.50.48
Pallas welding blanket, 400 x 400 cm	56.50.49
Part of a roll, width 100 cm	56.50.04.1000
Full roll 25 m <sup>1</sup> , width 100 cm	56.50.04.1025
Made to size welding blanket	56.50.40



Version 001 - Check our website for the latest version.

CEPRO\_PFS\_Welding blankets\_Basic\_Pallas\_1EN\_rev