

HERCULES WELDING BLANKET

Description

Hercules is a fiberglass fabric which is also treated with a grey flame-retarding PU coating (to increase the antislip properties and resistance to fraying) as well as an inorganic treatment to enhance the short-time temperature load.

Application

The maximum application temperature is 750 °C, shortly up to 900°C.

Conditions for use

- CEPRO recommends the use of multiple layers for maximum protection.
- Always use welding blankets at an angle of at least 15 degrees.
- The temperatures shown are only an indication. The suitability of the selected product should always be tested beforehand.
- Regularly check welding blankets for tears and or other damage. Replace damaged blankets where necessary.
- Welding blankets can be used for many purposes and therefore, no guarantee can be given on their use. The end user is responsible for determining whether the welding blanket is suitable for use in a specific situation and whether it offers sufficient protection during the work to be performed.
- CEPRO welding blankets are sewn on the cut edges with best quality Kevlar thread.

Characteristics

Hercules is recommended for horizontal use, for example as a welding and grinding blanket in situations in which high temperatures are reached.

Available dimensions

Hercules welding blanket, 100 x 100 cm	56.50.71
Hercules welding blanket, 200 x 100 cm	56.50.72
Hercules welding blanket, 200 x 200 cm	56.50.75
Hercules welding blanket, 200 x 300 cm	56.50.76
Hercules welding blanket, 300 x 300 cm	56.50.77
Hercules welding blanket, 400 x 300 cm	56.50.78
Hercules welding blanket, 400 x 400 cm	56.50.79
Part of a roll, width 100 cm	56.50.07.1000
Full roll 25 m ¹ , width 100 cm	56.50.07.1025
Made to size welding blanket	56.50.70



CEPRO_PFS_Welding blankets_Premium_Hercules_1EN_reVersion 001 - Check our website for the latest version.