# **INFOSHEET**



## CEPRO PVC WELDING CURTAIN

### Description

For the Olympus heat resistant fabric high quality silica fibres are used, which are environmen- for example as a welding and grinding curtain tally non-hazardous. Olympus is treated with a in situations in which very high temperatures mineral based finish to improve its abrasive are reached. Olympus silicate-fabrics have resistance and the resistance to fraying. Olympus is free of asbestos!

## **Application**

The maximum application temperature is 1000 °C, shortly up to 1300°C.

## **Conditions for use**

- CEPRO recommends the use of multiple layers for maximum protection.
- Always use welding blankets at an angle of at least 15 degrees.
- The temperatures shown are only an indication. The suitability of the selected product should always be tested beforehand.
- Regularly check welding blankets for tears and or other damage. Replace damaged blankets where necessary.
- Welding blankets can be used for many purposes and therefore, no guarantee can be given on their use. The end user is responsible for determining whether the welding blanket is suitable for use in a specific situation and whether it offers sufficient protection during the work to be performed.
- CEPRO welding blankets are sewn on the cut edges with best quality Kevlar thread.

## Characteristics

Olympus is recommended for horizontal use. excellent characteristics in relation to handling and resistance to high temperature loads. Therefore this fabric is suitable for use as welding blanket even under extreme conditions.

#### **Available dimensions**

56.50.91
56.50.92
56.50.95
56.50.96
56.50.97
56.50.99
56.50.992

Part of a roll, width 90 cm 56.50.09.0900 Full roll 50 m<sup>1</sup>, width 90 cm 56.50.09.0950 Made to size welding blanket 56.50.90





**Technical** Specifications 1/1

**Commercial 1/1** Certification 1/1 Safety 1/7