# INFOSHEET



## OMNIUM ECRAN DE SOUDURE

## Description

round pipe (30x2 mm) and rectangular pipe gloss ± 70% (40x30x2 mm) and are powdercoated colour grey RAL 7035.

## **Application**

When work needs to be regularly done in different places or when flexibility in the organization of the working space is required, protection with movable screens can offer a better alternative.

In addition, when one is not continuously using welding equipment, a screen offers a useful solution; after the work is done, the screen can quickly be removed from the work floor.

To apply pvc strips, curtains, sheets which can be fixed on the upper beam to obtain a separation. Omnium welding screens are placed on castors to make the screen mobile. There is also a possibility for building a closed cabin.

## **Conditions for use**

The Omnium welding screen can be handled by one operator and be fixed at one position to apply the brake option on two castors.

### **Characteristics**

The Omnium programme includes screens of a This welding screen contains welded carbon very high quality. The screens are made from steel parts, powder coated in grey RAL7035,

### **Technical information**

- The Omnium welding screen is supplied as an assembly kit in a strong cardboard box.
- Omnium welding screens are designed for indoor use
- The nuts and bolts used to connect the frame should be checked regularly
- You should regularly check the Omnium welding screen for tears and/or other damage. Replace damaged curtains or strips if necessary.



